

Model		LTAD-4060 /4070 /4080/4090/40100/40110/40120/40130/40140
Printing Area (W×L)	mm	Standard: 400×600 / 700 / 800 / 900 / 1000 /1100 / 1200 / 1300 / 1400 CCD version: 360×600 / 700 / 800 / 900 / 1000 / 1100 / 1200 / 1300 / 1400
Printing Speed	pcs/h	0–1,200, depending on machine configuration, print size and application requirements
Max. Screen Frame Size (W×L)	mm	700×950 / 1050 / 1150 / 1250 / 1350 / 1450 / 1550 / 1650 / 1750
Printing Table Size (W×L)	mm	500×900
Compressed Air Supply	MPa	0.4-0.6
Power Supply		Single-phase 220 V, 3 kW / Three-phase 220 V or 380 V, 3 kW; other power configurations available upon request
Screen Frame Adjustment Range	mm	Manual version: ±30 / Automatic version: ±20 / CCD version: ±20
Screen Lift Stroke	mm	200; optional 250 mm, 300 mm or custom stroke
Min. Distance Between CCD Registration Marks	mm	70
Max. Distance Between CCD Registration Marks	mm	Depends on machine size
CCD Field of View	mm	17×13
Net Weight	kg	Approx. 970 for the LTAD-4080; varies by model and configuration
Printing Table Height	mm	837; adjustable by +100 mm
Machine Dimensions (L×W×H)	mm	L: 1070 / 1170 / 1270 / 1370 / 1470 / 1570 / 1670/1770/1870×W: 1000×H: 1800 (1850); height adjustable by +100 mm