

|                                              |                                                          |                                                                                                                                                     |
|----------------------------------------------|----------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Model                                        | LTAD-7060 /7070 /7080/7090/70100/70110/70120/70130/70140 |                                                                                                                                                     |
| Printing Area (W×L)                          | mm                                                       | Standard: 700×600 / 700 / 800 / 900 / 1000 / 1100 / 1200 / 1300 / 1400<br>CCD version: 660×600 / 700 / 800 / 900 / 1000 / 1100 / 1200 / 1300 / 1400 |
| Printing Speed                               | pcs/h                                                    | 0–1,200, depending on machine configuration, print size and application requirements                                                                |
| Max. Screen Frame Size (W×L)                 | mm                                                       | 900×950 / 1050 / 1150 / 1250 / 1350 / 1450 / 1550 / 1650 / 1750                                                                                     |
| Printing Table Size (W×L)                    | mm                                                       | 800×900                                                                                                                                             |
| Compressed Air Supply                        | MPa                                                      | 0.4–0.6                                                                                                                                             |
| Power Supply                                 |                                                          | Single-phase 220 V, 3 kW / Three-phase 220 V or 380 V, 3 kW; other power configurations available upon request                                      |
| Screen Frame Adjustment Range                | mm                                                       | Manual version: ±30 / Automatic version: ±20 / CCD version: ±20                                                                                     |
| Screen Lift Stroke                           | mm                                                       | 200; optional 250 mm, 300 mm or custom stroke                                                                                                       |
| Min. Distance Between CCD Registration Marks | mm                                                       | 70                                                                                                                                                  |
| Max. Distance Between CCD Registration Marks | mm                                                       | Depends on machine size                                                                                                                             |
| CCD Field of View                            | mm                                                       | 17×13                                                                                                                                               |
| Net Weight                                   | kg                                                       | Approx. 1,300 for the LTAD-7060; varies by model and configuration                                                                                  |
| Printing Table Height                        | mm                                                       | 837; adjustable by +100 mm                                                                                                                          |
| Machine Dimensions (L×W×H)                   | mm                                                       | L: 1360 / 1460 / 1560 / 1660 / 1760 / 1860 / 1960/2060/2160×W: 1300×H: 1800 (1850); height adjustable by +100 mm                                    |